



01827 870250

Parking and access control equipment manufactured in the UK



Manual Barriers

PF5000S Manual Barrier



Manual Raise Arm Barriers are a low maintenance, cost effective way of manually controlling access to unathorised or controlled areas. We offer them in spans of up to 7 Metres (Standard Model).

The pivot assembly is made of steel box section, the zinc plated shaft pivots on two heavy-duty stainless steel bearing blocks.

The design of the PF5000S incorporates a locking mechanism, allowing you to fix the barrier in the raised or lowered position prior to applying the padlock. A counter balanced fish tail weight is fine tuned for ease of operation.

The PF5000S comes complete with a lockable end rest, padlock and keys.

Aluminium arm, finished in either alternate red and white or alternate yellow and black vinyl hatching as standard (other colours available.)

Standard Colours: Red/White or Yellow/Black.

PF5000S Features

- Robust Industry Proven Design to Secure your Car Park or Building Entrances & Exits.
- Can be Simply Locked in the Open or Closed Position.
- Can be Finished in your Corporate Colours.
- Durable Powder Coated Finish.
- Parts are Zinc Coated for Longevity.
- Smooth Easy Operation Allowing Almost Anyone with Guidance to Operate the Barrier.
- No Springs Needed A Perfectly Balanced Design.
- Comes Complete with M12 Anchor Shield Bolts & Fixed Lockable End Rest as Standard complete with an Exterior Rated Padlock.

Optional Extras

- Pogo Tip Support
- Stop/No Entry Signs
- Bottom Skirt











Parking and access control equipment manufactured in the UK



PF5000S Product Specification

Maximum Boom Length	7 Metres Plain Pole
Construction	Heavy Duty Steel Box Section
Finish	Zinc Plated & Polyester Powder Coated
Installation	Surface Mounted Ideal for Concrete Applications
Counter Weights	Steel PPC Counterweights
Product Weight	Standard Model - 54Kg (Excluding Counterweights)
Handing Options	Left or Right Handed (Optional)
Boom Diameter	Standard - 86mm x 60mm
Skirting Options	Standard - MAX 6 Metres
Ambient Humidity	-10 ~ 60 Degrees Centigrade
External Padlock	Padlock Brass 60mm Long Shackle c/w 3 Keys
Fixings	M12 Anchor Shield Bolts Included





