


POWER REQUIREMENTS	GENERAL NOTES	BOLT INFORMATION	DIMENSIONS & SPECIFICATIONS	OPTIONS
240v SINGLE PHASE SUPPLY 50hz 10A MCB, or 300mA RCD Type C Breaker	1.FOUNDATIONS MUST BE LEVEL/IN-LINE. 2.GATE MUST RUN LEVEL. 3.THERE MUST BE A MINIMUM CLEARANCE OF 100mm FROM THE ROAD TO THE BOTTOM OF THE GATE. 4.DUCT MUST BE RUN TO RECEIVER FROM PHOTOCELL. 5.IF IN DOUBT, PLEASE ASK!	INCLUDED- <u>MAIN TOWER:</u> 4 x M20 x 160MM THRU BOLTS	<u>FOUNDATIONS:</u> RECOMMENDED CONCRETE: C40 MIX. <u>MAIN TOWER:</u> L = 1300mm H = 1000mm. W = 1300mm.	SPIKE TOPPING OPTIONAL  SPIKE TOPPING NOT FITTED TO GATES 2.4M AND BELOW DRAWING DETAILS XM CLEAR OPENING - XM HEIGHT GEARBOX TYPE: HEAVY DUTY MESH INFILL COLOUR: REVISION DATE ORDER REFERENCE: ORDER NUMBER: E. & O. - ALL PICTURES AND SYMBOL DRAWING ARE FOR ILLUSTRATION PURPOSES ONLY ORIGINAL GATE DESIGN COVERED BY COPYRIGHT ©2012 ONWARDS