



GENERAL NOTES

1. FOUNDATIONS MUST BE LEVEL/IN-LINE.
2. GATE MUST RUN LEVEL.
3. THERE MUST BE A MINIMUM CLEARANCE OF 110mm FROM THE ROAD TO THE BOTTOM OF THE GATE.
4. DUCT MUST BE RUN TO RECEIVER FROM PHOTOCELL.
5. IF IN DOUBT, PLEASE ASK!

DIMENSIONS & SPECIFICATIONS

FOUNDATIONS:
 RECOMMENDED CONCRETE:
MAIN TOWER:
 L = 1300mm
 H = 1000mm.
 W = 1300mm.

POWER REQUIREMENTS

240v SINGLE PHASE SUPPLY
 50hz 10A MCB,
 or 300mA RCD Type C Breaker

BOLT INFORMATION

INCLUDED-
MAIN TOWER:
 4 x M20 x 160MM
 THRU BOLTS

OPTIONS

SPIKE TOPPING OPTIONAL

 SPIKE TOPPING NOT FITTED TO GATES 2.4M AND BELOW

1.	Revision 01	
No.	Revision/Issue	

XM CLEAR OPENING - XM HEIGHT
 GEARBOX TYPE: HEAVY DUTY
 ROUND BAR INFILL
 COLOUR:

ORDER REFERENCE:
 ORDER NUMBER:

Dwg Number: Single Swing Gate	Sheet 1.
Date:	

